



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : A61B 5/00	A1	(11) International Publication Number: WO 98/00056
		(43) International Publication Date: 8 January 1998 (08.01.98)
(21) International Application Number: PCT/US97/08337 (22) International Filing Date: 16 May 1997 (16.05.97) (30) Priority Data: 08/675,594 2 July 1996 (02.07.96) US (71) Applicant: VITALCOM, INC. [US/US]; 15222 Del Amo Avenue, Tustin, CA 92680 (US). (72) Inventors: FLACH, Terry, E.; 1676 E. Mendocine Street, Altadena, CA 91001 (US). STOOP, Michael, D.; 17 Dunlin Lane, Aliso Viejo, CA 92656 (US). (74) Agent: ALTMAN, Daniel, E.; Knobbe, Martens, Olson and Bear, 16th floor, 620 Newport Center Drive, Newport Beach, CA 92660 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

## (54) Title: ARCHITECTURE FOR TDMA MEDICAL TELEMETRY SYSTEM

## (57) Abstract

A medical telemetry system is provided for collecting the real-time physiologic data of patients (including ambulatory patients) of a medical facility, and for transferring the data via RF to a real-time data distribution network for monitoring and display. The system includes battery-powered remote telemeters (102A) which attach to respective patients, and which collect and transmit (in data packets) the physiologic data of the patients. The remote telemeters (102A) communicate bi-directionally with a number of ceiling-mounted RF transceivers (106), using a wireless TDMA protocol. The VCELLs (106), which are hardwire-connected to a LAN (116), forward the data packets received from the telemeters (102A) to patient monitoring stations (120) on the LAN (116). The VCELLs (106) are distributed throughout the medical facility such that different VCELLs provide coverage for different patient areas. As part of the wireless TDMA protocol, the remote telemeters (102A) continuously assess the quality of the RF links offered by different nearby VCELLs (by scanning the frequencies on which different VCELLs operate), and connect to those VCELLs which offer the best link conditions. To provide a high degree of protection against multi-path interference, each remote telemeter (102A) maintains connections with two different VCELLs (106) at-a-time, and transmits all data packets (on different frequencies and during different timeslots) to both VCELLs; the system thereby provides space, time and frequency diversity on wireless data packet transfers from the telemeters. The telemeters and VCELLs also implement a patient location protocol for enabling the monitoring of the locations of individual patients. The architecture can accommodate a large number of patients (e.g., 500 or more) while operating within the transmission power limits of the VHF medical telemetry band.





































































































